

The range is available in 2-5 screen models. The continuous movement of the rotary screen and the absence of vibration allows high precision cleaning on all types of conventional, organic or combined crops.

Perry & Musitelli also offer a wide range of screens compatible with rotary screen cleaners, which meet rigorous quality, durability and precision criteria while offering superior value for money.

Key benefits:

- Cleaning precision on all types of crops.
- Versatility from scalping to the finest sizing.
- Vibration free.

ENGINEERING



## Performance

Number

2

3

4

3

5

4

5

Grain

Feeder

Power Output (kW)

Cleaning

by

Aspiration

Pre-

Cleaning

Cleaning

by Aspiration

& Screen

Sizina

E1260

CR1262

CR1263

CR1264

ECR1263

ECR1264

ECR1265

CR1264

CR1265

Screen

Wheat

220tph

110tph

180tph

220tph

110tph

200tph

200tph

/ledium

Heavy

Waste

160tph

100tph

150tph

180tph

80tph

150tph

150tph

18tph

20tph



20%

Sun-

flower

80tph

35tph

65tph

80tph

35tph

70tph

70tph

Space Requirement

Width

16%

Peas

220tph

70tph

120tph

180tph

110tph

150tph

150tph

Height

10%

Rape-

seed

80tph

44tph

80tph

100tph

45tph

80tph

80tph

Length

Hiah

Moisture

Maize

130tph

90tph

130tph

200tph

110tph

130tph

130tph

Aspirator


Capacity

m³/H

## Musitelli Grain Cleaning Solutions 1260 Range







Fan



www.perryofoakley.co.uk sales@perryofoakley.co.uk +44 (0)1404 890300



www.perryofoakley.co.uk sales@perryofoakley.co.uk +44 (0)1404 890300

## Cleaner-Sizer - 1260 Range


The rotary screen cleaners separate usable grain from broken fragments & waste, and remove lightweight waste by aspiration.

The 1260 rotary screen cleaners consist of two distinct subassemblies: an E1260 cleaner and a CR1260 rotary screen with two to five screens depending on the model. These two units can be supplied separately.

Key benefits:

- Cleaning precision on all types of crops.
- Depressurisation of the screen, improving dust removal.
- Versatility: from scalping to the finest sizing.
- Vibration free.

Diagrams show large waste & straw, usable grain, broken fragments & heavy waste smaller than grain, medium-heavy waste, lightweight waste & dust & airflow.



## Rotary Screen - 1260 Range

The rotary screens can be used as precleaners or as a grader.

For pre-cleaning, the unit is operated in scalping mode to rapidly remove large waste materials contained in the grain. The screens allow the grain to pass through and the waste exits at the end of the screen unit.

For sizing, the screens separate out the grains according to size. For malting barley, they allow the tailings to pass through and the usable malting barley exits at the end of the screen unit.

Key benefits:

- Variable pitch as standard present on the entire range, increasing sorting precision.
- A large screen surface area.





The E1260 cleaners remove the grain of lightweight waste.

The aspirator creates a thin and uniform curtain of grain across the entire width of the unit, allowing a flow of air to be passed through it, which carries away all the very lightweight waste.

"Medium-heavy" waste materials are separated from fine dusts by the expansion of this air flow, and they are removed by an auger. The fine dusts are evacuated by the fan.

Key benefits:

- An optimised grain curtain height for enhanced efficiency.
- Every element is independently motor driven, with no pulleys or belts.
- Semi-heavy waste exits via the front which keeps the space required to a minimum.

