Rotary Cleaners - 630 Range

The range is available in 2-5 screen models. The continuous movement of the rotary screen and the absence of vibration allows high precision cleaning on all types of conventional, organic or combined crops.

Perry & Musitelli also offer a wide range of screens compatible with rotary screen cleaners, which meet rigorous quality, durability and precision criteria while offering superior value for money.

Key benefits:

- Cleaning precision on all types of crops.
- Versatility from scalping to the finest sizing.
- Vibration free.

PERRY



Performance

Screens

2

3

4

5

3

4

5

2

3

Δ

5

Mode

E600

CR632

CR633

CR634

CR635

CR633

CR634

CR635

CR632

CR633

CR634

CR635

Cleaning by

Aspiration

Pre-

Cleaning

Cleaning by

Aspiration

& Screen

Grading

15%

Wheat

40tph

15tph

20tph

30tph

35tph

15tph

25tph

30tph

Barley

30tph

10tph

15tph

20tph

25tph

10tph

18tph

20tph

1.5tph

2tph

2.5tph

3tph



15tph

4.5tph

9tph

13.5tph

15tph

6tph

9tph

10tph

Rapeseed Peas

40tph

18tph

27tph

36tph

45tph

18tph

24tph

30tph

35%

High

Moisture

Maize

25tph

7.5tph

15tph

22.5tph

30tph

10tph

15tph


20tph

Musitelli Grain Cleaning Solutions 630 Range





www.perryofoakley.co.uk sales@perryofoakley.co.uk +44 (0)1404 890300





www.perryofoakley.co.uk sales@perryofoakley.co.uk +44 (0)1404 890300




The rotary screen cleaners separate usable grain from broken fragments & waste, and remove lightweight waste by aspiration.

The 630 rotary screen cleaners consist of two distinct subassemblies: an E630 cleaner and a CR630 rotary screen with two to five screens depending on the model. These two units can be supplied separately.

Key benefits:

- Cleaning precision on all types of crops.
- Depressurisation of the screen, improving dust removal.
- Versatility: from scalping to the finest sizing.
- Vibration free.

Diagrams show large waste & straw, usable grain, broken fragments & heavy waste smaller than grain, medium-heavy waste, lightweight waste & dust & airflow.



Rotary Screen - 630 Range

The rotary screens can be used as precleaners or as a grader.

For pre-cleaning, the unit is operated in scalping mode to rapidly remove large waste materials contained in the grain. The screens allow the grain to pass through and the waste exits at the end of the screen unit.

For grading, the screens separate out the grains according to size. For malting barley, they allow the tailings to pass through and the usable malting barley exits at the end of the screen unit.

Key benefits:

2D Box

PERRY

ENGINEERING EXCELLENCE

- Variable pitch as standard present on the entire range, increasing sorting precision.
- A large screen surface area.









The E630 cleaners remove the grain of lightweight waste.

The aspirator creates a thin and uniform curtain of grain across the entire width of the unit, allowing a flow of air to be passed through it, which carries away all the very lightweight waste.

"Medium-heavy" waste materials are separated from fine dusts by the expansion of this air flow, and they are removed by an auger. The fine dusts are evacuated by the fan.

Key benefits:

- An optimised grain curtain height for enhanced efficiency.
- Every element is independently motor driven, with no pulleys or belts.
- Semi-heavy waste exits via the front which keeps the space required to a minimum.

